



MAXIMUM CAPACITY (LBS)			
WEB/ BLOCK	#10 SDS	UPLIFT P1	HORIZ P2
035	6	1460	485
	7	1700	485
	8	1930	485
046	5	2095	795
	6	2455	795
057	4	2050	1105
	5	2565	1105
	6	2940	1105

- 1) Min. screw spacing & edge distance = 9/16".
- 2) Min. bearing width = 3". Min steel thick = 0.054"
- 3) Welders and welding procedures shall be qualified as specified in AWS D1.3.
- 4) Min. filler metal strength, Fxx = 70 ksi.
- 5) When this connection detail is applied to both plies of a 2-ply truss, the capacities double.
- 6) This detail does not indicate or imply that the depicted bearing is structurally adequate for the loads shown. Design of bearing is required.
- 7) Max. Reactions shown are non-concurrent



METAL FRAMING a division of MITEI®
www.AEGISMETALFRAMING.COM
 14515 N. Outer 40 Drive Suite 110
 Chesterfield, MO 63017
 Phone:866/902-3447 Fax:314/434-5234

USC TRUSS TO BEARING CONNECTION
 USJ - CFS

DETAIL NO.

C-CFS-2

CATEGORY

STANDARD DETAILS

DATE

3/3/09